



MATERIAL HANDLING

DRAG CONVEYORS

FEATURES

- Capacities up to 50,000 BPH (62,500 CFH)
- AGMA direct drives with Nema Adaptors
- Premium efficiency motors
- Heavy duty roller or welded chain with steel attachments and bolted UHMW paddles
- C1045 superior shafting
- Split hardened tooth sprockets
- High duty cycle bearings
- ACME take-up screws
- Heavy duty mild steel construction

OPTIONS

- Stainless steel housings
- Spring style tail take-ups
- Continuous return rails or return idler rollers
- Intermediate discharge gates
- AR, Hardox liners

BELT CONVEYORS

FEATURES

- Capacities up to 45,000 BPH (56,250 CFH)
- AGMA direct drives with Nema Adaptors
- Premium efficiency motors
- Heavy duty rubber belting
- CEMA troughing and return idlers
- C1045 superior shafting
- Drum and wing type pulleys
- Heavy duty roller bearings
- Heavy duty mild steel construction

OPTIONS

- Stainless steel housings
- Gravity boot take-ups
- Mine duty pulleys

SCREW CONVEYORS

FEATURES

- Capacities up to 30,000 BPH (37,500 CFH)
- AGMA direct drives with Nema Adaptors
- Premium efficiency motors
- Intermediate hanger bearings
- C1045 superior shafting
- Heavy duty ball bearings

OPTIONS

- U trough or Tube Feeder
- Stainless steel troughs
- Variable pitch flighting for feeder applications
- Stainless steel screws and shafts
- Intermediate gates, Inlet, hoppers

BUCKET ELEVATORS

FEATURES

- Capacities up to 75,000 BPH (93,750 CFH)
- AGMA direct drives with Nema Adaptors
- Premium efficiency motors
- Standard internal backstops
- Screw T-U Boots, ACME Rod
- Heavy duty rubber belting
- Superior quality polyethylene buckets
- C1045 superior shafting
- Crown Face Drum and wing type pulleys
- Heavy duty roller bearings
- Heavy duty mild steel construction
- NFPA explosion venting

OPTIONS

- Stainless steel housings
- Gravity boot take-ups
- Self-cleaning boots, liners, access ladders and platforms OSHA vented, nylon, polyurethane and steel bucket options, bucket catchers
- Mine duty pulleys



DISTRIBUTORS

FEATURES

- Spouting sizes range from 10" to 16" diameter
- Configurations from 4 to 24 outlet spouts (depending on spout size)
- AGMA Class 2 direct coupled drives
- Premium efficiency motors
- High quality position switches
- Heavy duty mild steel construction

OPTIONS

- Stainless steel construction
- Flat back or full round configurations
- Spout liners for abrasion resistance
- Independent electric control panels

GATES

FEATURES

- Standard size up to 36" x 36"
- Available with manual, electric, pneumatic and hydraulic operators
- Heavy duty and racks and pinion gears on manual and electric models
- High quality position switches
- Heavy duty mild steel construction

OPTIONS

- Stainless Steel Construction
- Custom Sizes available
- AR, Hardox, ceramic liners

VALVES

FEATURES

- Flop valve standard sizes up to 16" diameter
- Synchronized valve standard sizes up to 36"
- Available with manual, electric, pneumatic and hydraulic operators
- Heavy duty rack and pinion gears on manual and electric synchronized models
- High quality position switches
- Heavy duty mild steel construction

OPTIONS

- Stainless steel construction
- Custom sizes available
- AR, Hardox, ceramic liners





VIS 

Box 405, 140 Parkland Road Oak Bluff, Manitoba Canada R4G 0A5
204.897.6949 info@vis-aggrowth.com vis-aggrowth.com

AGI 
AG GROWTH INTERNATIONAL